



Gypshree™

AN ISO 9001:2015, ISO: 14001:2015, ISO 4200:2018

घर से हो जाये
प्यार!



Bringing
Color
To Life





Gypshree™ Acrylic DISTEMPER

INTERIOR & EXTERIOR

All Previous coating of Gypshree Acrylic Washable Distemper or lime wash must be removed. Ensure surface is dry & free from dirt before application of Gypshree Acrylic Washable Distemper. Apply a coat of Cement Primer for proper surface. Gypshree Acrylic Washable Distemper is applied as a thick paste. Thin 1kg Gypshree Acrylic Washable Distemper with 500-600ml. of water. Slowly add water while continuing to stir the mixture. Add 2-3 coats with brush, with minimum drying time of 3-4 hours between coats.

KEY FEATURES

- ▶ Economical.
- ▶ Smooth Finish.
- ▶ Eco Friendly.
- ▶ Low VOC.
- ▶ Good Coverage.
- ▶ Extra Whiteness



Gypshree™ WATER THINNABLE WALL PRIMER

INTERIOR & EXTERIOR

Gypshree Wall Primer has been manufactured for above grade masonry surfaces where a high performance primer is needed. It is efflorescence and alkali resistant and will increase and reinforce the performance of the paints. It can be used on properly prepared concrete, concrete block, brick and stucco. Gypshree Wall primer is also designed for use on exterior wood and plywood siding and trim. It can be used for priming new or previously painted walls, ceilings & wooden surfaces.

KEY FEATURES

- ▶ Moisture resistant.
- ▶ Resists scuffs & stains.
- ▶ Antimicrobial fungus resistant coating.
- ▶ Stains wash off easily, superior scrubability.



Gypshree™ Instant Plaster Bond

INTERIOR & EXTERIOR

Gypshree Instant Plaster Bond is formulated with Instant Bonding Polymer which makes it an excellent bonding agent suitable for RCC background and internal gypsum or plaster based wall lining. The unique mix of polymers, selected sand fillers and additives makes it coarse and improves its bonding properties.

Benefits



Strong Durable Bonding



Suitable for RCC, Gypsum and Sand Cement Plaster



Easy Single Coat Application

Features



Dual bonding - chemical as well as mechanical grip



Can be applied using both brush and roller



Green colour for easy identification



Gypshree™ White Cement Based WALL PUTTY

INTERIOR & EXTERIOR

Gypshree Wall Putty is a white cement based product with redispersible polymer and functional additives. It gives interior and exterior rough plasters a smooth finish. It can be used on interior as well as exterior surfaces like cement plasters, asbestos sheets, concrete, and brickwork. It can also be treated as a base coat for painting. It is manufactured under strict quality-controlled environment using state-of-the-art automatic SCADA/PLC controlled machines.



- 
SURFACE PREPARATION
- 
CLEANING
- 
THINNING RATIO
- 
MIXING
- 
APPLY 2 COAT



Gypshree™ Decorative WHITE CEMENT

INTERIOR & EXTERIOR

White cement for multi-purpose usage such as wall decoration with a variety of techniques. This product can also be used for installing and grouting tiles, or for sanitary ware installation with good adhesiveness and reasonable setting time. Additionally, this product can also be used for beautiful and durable stucco or moulding works that need no bearing capacity.

- 
SURFACE PREPARATION
- 
CLEANING
- 
THINNING RATIO
- 
MIXING
- 
APPLY 2 COAT




Gypshree™ Gypsum Plaster P.O.P

INTERIOR & EXTERIOR

Gypshree Plaster is one of the best-selling products in the Gypsum Plaster Segment. Expert Plaster provides extra whiteness and expands coverage. What makes Gypshree Plaster the best is the scientific research involved in producing this international standard product. Our research and development team ensures the use of the best raw material from best gypsum mines so that it doesn't crack or shrink after hardening. Also, the slow drying helps it become durable and long-lasting. Once applied, it will protect and beautify the building for years and without any constant maintenance

- 
Super White & Super Strength
- 
Extra Coverage
- 
Made From Indian & Imported Gypsum
- 
Special Power Packing



Gypshree™ Gypsum Jointing COMPOUND

INTERIOR & EXTERIOR

Gypshree Pro-Fill is an Air-Drying jointing compound used for plasterboard finishing at vertical & horizontal joints. It is also used for filling the uneven gaps, small cut-outs and finishing of the internal and external corner joints.

KEY FEATURES

- ▶ Air Drying Drying Time Depends
- ▶ Excellent Workability
- ▶ On Temperature & Humidity
- ▶ Excellent Bond Strength And Higher Crack Resistance
- ▶ Minimum Or No Shrinkage
- ▶ Zero/ Minimum Wastage





Gypshree™
AN ISO 9001:2015, ISO: 14001:2015, ISO 4200:2018

Finder 

www.gypshree.com



MKTD. BY
SHREE INDUSTRIES

A/4, Bhankri Ashram Road, Faridabad, Haryana-121004 (INDIA)

 shreeindustries2015@gmail.com **TOLL FREE NO. 18003092042** 

